SPB100 Intelligent Solar LED Bollard





The SPB100 solar powered LED bollard is an architectural independent lighting solution ideally for various aplications as in parks, pathways, bike lanes, remote areas, golf course, beach resorts, marina's, residential areas and landscape lighting projects.

Based on the ecological principle: there is only light needed when someone is present. An integra-ted system detects pedestrians and cyclists and switches on a cluster of light moving in their direction.

The architectural patented design in combination with a robust high LED lighting output in a high grade construction, makes it your ideal choice for all you self-contained lighting projects.

A unique built-in software and wireless radio system makes the SPB100 suitable in bird/bat wildlife sensitive areas. Because there is only light by human presence and activity. (lumen on demand.)

SPB100 works completely without wiring and gets its power from the sun, using a special energy storage system, which requires no replacement of batteries for several years.

Energy harvesting and usage is controlled by a unique builtin self-decisive software algorithm. Cloudy days or shaded areas, the intelligent energy saving SPB100 always provides perfect lighting conditions.



Residential areas	
Parks	
Boardwalks	
Resorts	•
Marinas	
Gardens	•
Landscaping	
Walking paths	
Bike paths	•
Golf courses	•







Legal Clarification: All technical information and/or products listings and/or technical support, and/or any kind of graphics, illustrations and/or instructions and/or the names, trade names, trademarks, trade symbols, service marks, logos, icons and trade dress of SolarPath In cor in connection to SolarPath In cor any of its selling products, contained herein is in the exclusive ownership of SolarPath Inc and may not be alternated and/or used in any manner including but not limited to copy of some or all of the said material by users and/or viewers or any third party for that matter of this document and the website to which it is linked without the express prior written permission of SolarPath Inc. Furthermore, redistribution or any kind of commercial use or alternation or any kind of use other then downloading presented information in some or all contents of downloadable documents, and/or downloadable contents, is strictly prohibited without express written prior permission. All information set out herein is subject to changes as may occur from time to time. SolarPath Inc is not responsible for, and cannot guarantee and shall not be held liable for any information or the accuracy of such in websites that it does not manage.



Technical Specifications

LED and Optics	
Lighting Technology	Rebel 3 x 3 Watt Max 130 lm/W Neutral white 4500 kelvin
Life span	50.000 Hours
Optics	6°/15°/30°
Solar Module	
	Polycarbonate protected PV panels
	3 x 5.4 Watt (tot. +/- 16 Watt)
	Hi class mono cells
	Integrated in mechanical construction
	Anti theft & vandal proof
Intelligent Controls	
	Built-in intelligent MPPT charger
	Presence detector 13 ft, −120°
	Led driver - defaults to 3 Watt (9W max.)
	Zigbee radio controlled
	Eyes curve light management
	Energy harvesting management
	Light output management
Included Battery Options	
	• Lifepo4 2000 cycles Temperature - 20 + 65°C (-4 +149F°)
	• Eco battery 1.000.000 cycles - 40 +65°C (-40 +149F°
Materials	
Body	Anodized aluminium 25u satin gray
	Anti theft stainless security screws
	Mounting bracked included
	Ral powder colors possible on request
	Eco design

