



The SolarPath HighLight SUNLIGHT™ Series is the ideal LED solar illumination technology for parking lot, street, pathway, perimeter and site lighting applications. Utilizing mesh networking, high output LEDs, and ultra efficient solar panels—all while maintaining its compact design—the HighLight SUNLIGHT™ offers unparalleled balance of cost and performance.

### Key features:

- Compact design for easy and safe installation
- Ultra-bright homogeneous LED light distribution
- Strong, weather-proof housing design
- Vandal resistant
- Recommended installation height 20ft (6m)
- Complies with Fish & Wildlife conservation regulations

### Uses and Applications Guide

Streets lighting	●
Parking lots	●
Boardwalks	●
Farms	●
Public parks	●
Private gardens	●
Access roads	●
Walking paths	
Bus stations	



Legal Clarification: All technical information and/or products listings and/or technical support, and/or any kind of graphics, illustrations and/or instructions and/or the names, trade names, trademarks, trade symbols, service marks, logos, icons and trade dress of SolarPath Inc or in connection to SolarPath Inc or any of its selling products, contained herein is in the exclusive ownership of SolarPath Inc and may not be alternated and/or used in any manner including but not limited to copy of some or all of the said material by users and/or viewers or any third party for that matter of this document and the website to which it is linked without the express prior written permission of SolarPath Inc. Furthermore, redistribution or any kind of commercial use or alternation or any kind of use other then downloading presented information in some or all contents of downloadable documents, and/or downloadable contents, is strictly prohibited without express written prior permission. All information set herein is subject to changes as may occur from time to time. SolarPath Inc is not responsible for, and cannot guarantee and shall not be held liable for any information or the accuracy of such in websites that it does not manage.

### Technical Specifications

Lighting and Operation	
Lighting Technology	LED Street Light Technology
Brightness	up to 1,200 lumens
Default color temperature	5,500K (other may be available)
Available distribution types	II, III, IV, V
Standard operation features	<ul style="list-style-type: none"> <li>• Automatic day/night detection</li> <li>• Battery deep discharge and overcharge protection</li> <li>• False activation prevention logic</li> <li>• Computerized self-learning seasons change detection</li> <li>• Auto-adjusting battery charge algorithm according to ambient temperature sensing</li> </ul>
Operation time	up to 72 hours (per charge cycle, programming dependent)
Energy Collection and Storage	
Solar panel type	Mono Crystalline Silicon, 60W
Battery type	Extreme temperature Deep Cycle AGM / Gel-Cell
Voltage / Current	12VDC
Materials	
Body	Steel or Aluminum
Dimensions (main body)	L30.2" W 26" H12.9" / L76.7cm W66.4cm H32.8cm
Dimensions (pole mount diameter)	Inner: 2.46" / 6.25cm
Unit Weight	Aluminum 28.66lb / 13kg Steel 79.37lb / 36kg
EPA	5

### Optional Features

SP Control™ package	Allows full control of the system, alarms and event monitoring and statistical information transmission over long range, secure wireless connection.
---------------------	--