



The Solar Outdoor Solar Light allows for charging for all your different devices that are needed. This fits on top of any device such as kiosks, tents, or any outdoor material.

## Key features

- The solar controller and battery are built-in light head.
- Cost of remote control is included.
- IFEPO4 battery is optional
- 5M cable with MC4 plugs to connect light and solar panel, extended length of cable is available.
- Lighting time can be changed freely by remote control.
- Beam angle: 240 Degree as bat wing distribution.

## Uses and Applications Guide

Streets lighting	●
Parking lots	●
Boardwalks	●
Farms	●
Public parks	●
Private gardens	●
Access roads	●
Walking paths	●
Bus stations	●



Legal Clarification: All technical information and/or products listings and/or technical support, and/or any kind of graphics, illustrations and/or instructions and/or the names, trade names, trademarks, trade symbols, service marks, logos, icons and trade dress of SolarPath Inc or in connection to SolarPath Inc or any of its selling products, contained herein is in the exclusive ownership of SolarPath Inc and may not be alternated and/or used in any manner including but not limited to copy of some or all of the said material by users and/or viewers or any third party for that matter of this document and the website to which it is linked without the express prior written permission of SolarPath Inc. Furthermore, redistribution or any kind of commercial use or alternation or any kind of use other than downloading presented information in some or all contents of downloadable documents, and/or downloadable contents, is strictly prohibited without express written prior permission. All information set out herein is subject to changes as may occur from time to time. SolarPath Inc is not responsible for, and cannot guarantee and shall not be held liable for any information or the accuracy of such in websites that it does not manage

## Technical Specifications

	SP-XL12	SP-XL-18	SP-XL24	SP-XI36
Fixture IP	IP67	IP67	IP67	IP67
LED House	3.6 x 3.3 x 23.6in	3.6 x 3.3 x 23.6in	3.6 x 3.3 x 47.2in	3.6 x 3.3 x 47.2in
LED Type	LED	LED	LED	LED
Color Temperature	3000K~6500K	3000K~6500K	3000K~6500K	3000K~6500K
LED Power	12W	18W	24W	36W
Lumen	1500lm	2200lm	3000lm	4200lm
Lighting Angle	240°	240°	240°	240°
Sensor	Yes	Yes	Yes	Yes
Battery Capacity- Li(NiCoMn)O2	144WH 11.1V	200WH 11.1V	288WH 11.1V	433WH 11.1V
Controller Type	PWM	PWM	PWM	PWM
Solar Panel	40W 18V Mono	50W 18V Mono	60W 18V Mono	80W 18V Mono
Panel Size	26.3 x 16.5 x 1.8in	27.5 x 21 x 1.1in	26.3 x 23.2 x 1.1in	29.9 x 23.2 x 1.1in
Warranty	2 years	2 years	2 years	2 years

	SP-XL48
Fixture IP	IP67
LED House	3.6 x 3.3 x 23.6in
LED Type	LED
Color Temperature	3000K~6500K
LED Power	48W
Lumen	5500lm
Lighting Angle	240°
Sensor	Yes
Battery Capacity- Li(NiCoMn)O2	577WH 11.1V
Controller Type	PWM
Solar Panel	100W 18V Mono
Panel Size	39.3 x 26.3 x 1.1
Warranty	2 years

