


LED CANOPY LIGHT

SHINE Series



The SHINE Series, featuring its patented, innovative installation and flush-mount design, is perfectly suitable for gas station lighting or other applicable mounting.



FEATURES & BENEFITS

- Ideal solution for gas station lighting application.
- Slim appearance with 25mm thickness.
- Modular design allows for easy installation, replacement and maintenance.
- Precision lens system provides optimized illumination for intended area.
- Flush mount to ceiling to prevent the build-up of dust on the fitting.
- Multiple lighting control options are available, e.g. DALI, 1-10V.
- 10 years limited warranty available.

CERTIFICATIONS

UL/ CUL/ DLC/ LM79/ CB/ CE/ RoHS/ IK08

TECHNICAL PARAMETERS

Power	120/160W
Input	120-277VAC or 220-240VAC or 347-480VAC
PF	>0.95
THD	<20%
L85	>60,000H
Operating Temperature	-40F- 122F
Efficacy	120-140lm/W
ANSI CCT	3000K/4000K/5000K/5700K
Min CRI	70* or 80 or 85
IP Rating	IP67
SPD	Optional
DALI	Optional
1-10V	Optional
Photocell	Optional
Smart Control	/
Optic (IESNA)	Type I, Type II, Type III, Type IV, Type V
Color Options	White

* Standard

ORDERING INFORMATION

Example : CLA120-T5S-50K-GR-00

MODEL (Nominal Power)		MOUNTING	OPTIC LENS	CCT (ANSI)	OPTIONAL COLOR	LIGHTING CONTROL	ACCESSORY INFO
120-277VAC or 220-240VAC	347-480VAC						
CLA120 CLB160	CLA120H* CLB160H*	/	T1M T2M T3M T3L T4S T4M T5U T5V T5W T5S T5M T5L T5X	30K ★ 40K ★ 50K 57K	★ WH	00 Not required 04 DALI 05 1-10V dimming	10KA/20KA Surge Protection Device Back Light Shield

* DALI unavailable

★ Regularly stocked item