# 2SPBL11 Architectural Solar LED Light





The 2SPBL11 solar bollard light is an architectural independent lighting solution ideally for various applications such as parks, pathways, bike lanes, remote areas, golf courses, beach resorts, marinas, residential areas and landscape lighting projects.

The architectural patented design in combination with a robust high LED lighting output in a high-grade construction makes it your ideal choice for all your self-contained lighting projects.

2SPBL11 works completely without wiring and gets its power

from the sun, using a special energy storage system, which requires no replacement of batteries for several years.

Energy storage and usage is controlled by a unique built-in self-decisive software algorithm. Cloudy days or shaded areas, the intelligent energy saving 2SBL11 always provides perfect lighting conditions.

## Uses and Applications Guide

| Residential areas |  |
|-------------------|--|
| Parks             |  |
| Boardwalks        |  |
| Resorts           |  |
| Marinas           |  |
| Gardens           |  |
| Landscaping       |  |
| Walking paths     |  |
| Bike paths        |  |
| Golf courses      |  |

#### ORDERING GUIDE

### Example: 2SPBL11-30K-0-GR



SolarPath inc of in connection to SolarPath inc of any of its selling products, contained interin is in the exclusive ownership of SolarPath inc and may not be alternated and/or used in any manner including but not limited to copy of some or all of the said material by users and/or viewers or any third party for that matter of this document and the website to which it is linked without the express prior written permission of SolarPath Inc.

Furthermore, redistribution or any kind of commercial use or alternation or any kind of use other then downloading presented information in some or all contents of downloadable documents, and/or downloadable contents, is strictly prohibited without express written prior permission. All information set out herein is subject to changes as may occur from time to time. SolarPath Inc is not responsible for, and cannot guarantee and shall not be held liable for any information or the accuracy of such in websites that it does not manage

www.solarpathusa.com | 1 888 333 SOLAR





## **Technical Specifications**

| 6.4V/5Ah<br>LifePO4 Battery, more then<br>2000 cycles |
|---|
|   |
| 2000 cvcles   |
|   |
| 3W (440lm-500lm)                                      |
| 39.37in   |
| Depends on solar radiation                            |
| 5°F- 149°F  |
| 30% dim, when motion sensor                           |
| trigger 100% to 30 sec.                               |
| Chip LED, Beam angle 120°                             |
| 50.000 Hours  |
| 3,000К — 6,000К                                       |
| Monocrystalline solar panel                           |
| IP65  |
| Anodized aluminum alloy                               |
|   |

