HIGHLIGHT ML-GL-U



The SolarPath HIGHLIGHT $ML\text{-}GL\text{-}U^{\text{\tiny{TM}}}$ is the premier LED solar illumination technology in its class today. Ultra- bright/High Intensity LED lighting means a total lighting solution for any need. This product has both a solar engine and a flood light. The ML-GL-U's battery and control is attached to solar panel which allows this product to be used for field, sign, warehouses, roofs, ground and on walls.

Key features:

- Low installation and maintenance costs.
- Replaceable Battery.
- IP65 Rating.
- High performance 1W LEDs with 150lm/w.
- Light dimming engine.
- Led's operating life time over 100,000 hours at maximum output.
- PTC Auto-heating system.
- LED strings shunt protection.
- Ideal for solar or energy saving electrical applications.
- Aluminum housing for efficient heat dissipation

Uses and Applications Guide

Warehouse	
Tents	
Boardwalks	•
Monuments	
Signs	
Gardens	





Technical specifications

	Туре	Monocrystalline Silicon			
Solar Module Parameters	Power	Up to 75W			
Solar Charge Controller	Туре	MPPT			
Parameters					
Battery Parameters	Туре	Li-ion			
-	Capacity	Up to 60AH			
	Light Source Power	Up to 12W each			
	Lamp Rated Total Luminous	Up to 1,600lm(each)			
	Flux				
	Luminous Efficacy	135lm/w			
ED Light Parameters	Input Voltage	DC24V			
	CCT (Correlated Color	3,000K-6,000K			
	Temperature)				
	Color Rendering Index (CRI)	≥82			
Operation profiles	Programmable, depend on solar radiation.				
Lighting Material	Die-casting Aluminum + Stainless steel				



Ordering Guide: EXAMPLE: HIGHLIGHT ML-GL-U-45W-12W-A-3-1-30K-18AH-BLK-PTC-GM

Model	Solar Panel	LED Power	LED Qty.	Distribution type	LED Color Temp	Battery Options	Body Color	Options
HIGHLIGHT-ML-GL-U	45W	12W	A- 1 pc	1- Type I	30K	18AH	BLK- Black	PTC-Auto-heating system
	60W		B- 2 pcs		40K	25AH		GSM - Ground spike mounting
	75W		C- 3 pcs		50K	30AH		GUM- Ground U mounting
					60K	45AH		
						60AH		







