Garden Light™





Solar Tracking





Advantages

- Controller: Dedicated controller, remote control, optically control, time control, anti-overdischarge and short-circuit resistance.
- Materials: Aluminum alloy pole powder-coated with electrostatic spray for anti-salted, anti-acid, rust resistant. Adopt PMMA lampshade material, nanometer anti-glare process. Solar panel mounting rack made by high regidity polymer materials.
- Work Time: Optically controlled automatically turn on & off the lights.
 Maximum brightness work for four hours, and then turns to half of the brightness until dawn.
- Smart Tracking: Automatic tracking function with high accuracy and reliability. Solar efficiency is increased by 20%-40%.
- Solar Tracking







Legal Clarification: All technical information and/or products listings and/or technical support, and/or any kind of graphics, illustrations and/or instructions and/or the names, trade names, trade arms, trade symbols, service marks, logos, icons and trade dress of SolarPath Inc or in connection to SolarPath Inc or any of its selling products, contained herein is in the exclusive ownership of SolarPath Inc and may not be alternated and/or used in any manner including but not limited to copy of some or all of the said material by users and/or viewers or any third party for that matter of this document and the website to which it is linked without the express prior written permission of SolarPath Inc. Furthermore, redistribution or any kind of commercial use or alternation or any kind of use other then downloading presented information in some or all contents of downloadable documents, and/or downloadable contents, is strictly prohibited without express written prior permission. All information set out herein is subject to changes as may occur from time to time. SolarPath Inc is not responsible for, and cannot guarantee and shall not be held liable for any information or the accuracy of such in websites that it does not manage.

Technical Specifications 2SPG120B

Solar Power	54W±15%
Battery Capacity	14.8V/41.6Ah
Battery Type	Li-ion Battery
Total Light of Power	15W
Color Temperature	4000K
Working Temperature	-4"F-131F"
Height	13.7FT
Road Width	13ft-19.6ft
Wind Resistance	27m/s
Rainy/Cloudy Days	2-3Days
Distance Between Light(Recommendation) 39.3FT-59FT	

The Application

