



The SolarPath HighLight HL-SL-AUR™ is the premier LED solar illumination technology in its class today. Ultra-bright/High Intensity LED lighting means a total lighting solution for any need. This product has both a solar engine and a flood light. The HL-SL-AUR's battery and control is on the LED head which allows this product to be used for warehouses, roads, roofs, and on walls. Once the product is installed, it can be controlled via a remote control.

Key features:

- Low installation and maintenance costs.
- IP67 Rating.
- High performance Cree 1W LEDs with 140lm/w.
- Light dimming engine.
- LED's operating life time over 150,000 hours at maximum output.
- Dedicated optical lens per LED for enhanced spread and uniformity.
- LED strings shunt protection.
- Ideal for solar or energy saving electrical applications.
- Battery enclosure
- Aluminum housing for efficient heat dissipation
- Approved IDA
- LM 79/80

Uses and Applications Guide

Mid-size roads	●
Warehouse	●
Tents	●
Boardwalks	●
Farms	●
Public parks	●
Private gardens	●
Access roads	●
Walking paths	●
Walking paths	●

Technical Specifications

Lighting and Operation

Lighting Technology	LED Street Light Technology
Brightness	Up to 8,400 Lumen
Color temperature	5,500°K (other may be available upon request)
Available distribution types	I, II, III, IV, V
Standard operation features	<ul style="list-style-type: none"> • Automatic day/night detection • Battery deep discharge and overcharge protection • False activation prevention logic • Computerized self-learning seasons changedetection • Auto-adjusting battery chargealgorithm accordingto ambient temperature sensing
Operation time	up to 72 hours (per charge cycle, programming dependent)

Battery Enclosure	Mount on the ground, on a roof, on a wall
-------------------	---

Energy Collection and Storage

Solar panel type	Mono/ Poly Crystalline Silicon
Battery type	Lithium
Voltage / Current	12VDC

Materials

Body	Galvanized Steel/Stainless steel and Aluminum
Dimensions (main body)	Depends on configuration
Unit weight	Depends on configuration
EPA	Depends on configuration
IP Rating	IP67

Optional Features

Integrated Motion Option	Allows for flexible energy saving programming for location with low insolation levels and extreme weather conditions.
--------------------------	---

Ordering Guide

EXAMPLE: HL-SL-AUR-A-45W-B-15W-1-30K-192WH-GR-00

Model	Solar Panel Quantity	Solar Panel	LED Qty	LED Power	Distribution type	LED Color Temp	Battery Options	Body Color	Options
HL-SL-AUR	A- 1 Panel	45W	A-1pc	15W	1- Type I	30K	192WH	GR- Gray	00 - not required
	B- 2 Panel	60W 80W 100W 120W 140W 180W 200W	B-2pcs	20W 30W 50W 60W	2- Type II 3- Type III 4- Type IV 5- Type V	35K 40K 50K 57K	312WH 432WH 680WH		01 - motion sensor

